



Technical tables JIP™ ball valves

JIP™ ball valves for building installation

Type	DN [mm]	PN [bar]	Max temp. [°C]	Connection type
JIP™ Standard	15-50	40	180°C	Welded/Welded
	65-600	25		
	15-50	40		Flange/Flange, Flange/Welded
	65-600	16 / 25		
	15-50	40		Internal thread, Internal thread/Welded
	JIP™ Full bore	15-50		40
65-400		25		
15-50		40	Flange/Flange, Flange/Welded	
65-400		16 / 25		
20-50		40	Internal thread, Internal thread/Welded	
JIP™ House Insertions (Twins)	15-50	40	180°C	Welded/Welded, Internal thread/ Welded Internal thread/Internal thread,
JIP™ Copper	15-50	10 / 16	130°C	Copper, Copper/Welding, Internal thread/Welding
JIP™ Specials	15-50	40	180°C	Detachable ends, Welding/External thread

JIP™ underground ball valves for pre-insulation

Type	DN [mm]	PN [bar]	Max temp. [°C]	Connection type	Actuation
JIP™ Underground	20-600	25	180°C	Welded/Welded	Hexagon stem (T-Handle)
					Gear Flange
					Worm and Bevel Gear
JIP™ Service Valves	20-100	25	180°C	Welded	Hexagon
JIP™ Hot Tap	20-50	40	180°C	Welded/Welded	Allen key, L-handle
	65-100	25			
JIP™ Branching	20-50	40	180°C	Welded/Welded,	Allen key. Hexagon
	65-100	25		Internal thread/Welded	